

# ALPINE® Racing 4T 5W-50

**High performance engine oil for 4-stroke motorcycle engines**

## Properties

- Exceptional wear protection
- Excellent shear stability
- Optimised friction properties
- Outstanding low temperature performance
- Excellent detergent/dispersing behaviour
- Also suitable for wet clutches
- Effective rust and corrosion protection
- For optimum motor protection

## Application notes

**ALPINE Racing 4T 5W-50** is especially recommended for the lubrication of 4-stroke motorcycle engines in high-performance motorcycles, even under extreme operating conditions (race track and road).  
**Observe manufacturer's instructions.**

## Service description

### Specifications:

- API SN
- JASO MA2

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Racing 4T 5W-50
Density at 15°C	DIN 51 757	kg/m³	863
Viscosity at 40°C	DIN 51 562	mm²/s	108
Viscosity at 100°C	DIN 51 562	mm²/s	18.0
Viscosity index (VI)	DIN ISO 2909	-	185
Viscosity at -30°C	DIN 51 377	mPa.s	5770
Pour point	DIN ISO 3016	°C	-39
Flash point COC	DIN ISO 2592	°C	226
Base number	DIN ISO 3771	mg KOH/g	10.5

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.