

ALPINE® 2-T

Two-stroke engine oil

Properties

- Two-stroke engine oil on mineral oil basis
- Good protection against rust, corrosion and wear
- Stable lubricating film prevents piston jamming and seizing
- Offers protection against deposits and plug bridging
- Use in systems with separate and mixed lubrication
- Environmentally friendly due to low smoke emission

Application notes

ALPINE 2-T is a universal two-stroke engine oil for air and water-cooled two-stroke engines in motor vehicles, motorcycles, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.

Observe manufacturer's instructions.

Service description

Specifications:

- API TC
- ISO-L-EGD
- JASO FB

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE 2-T
Density at 15°C	DIN EN ISO 12185	kg/m ³	878
Viscosity at 40°C	DIN ISO 51 562	mm ² /s	76.4
Viscosity at 100°C	DIN ISO 51 562	mm ² /s	9.6
Viscosity index (VI)	DIN ISO 2909	-	103
Pour point	ASTM D 7346	°C	-21
Flash point COC	DIN ISO 2592	°C	192

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.