

ALPINE® PSA 0W-20

HC-synthetic high-performance low viscosity engine oil

Properties

ALPINE PSA 0W-20 is a HC-synthetic high-performance low viscosity engine oil for petrol and diesel engines in passenger cars with low sulfur, ash and phosphorus content (low SAPS).

ALPINE PSA 0W-20 ensures excellent cold start behavior at low temperatures, fuel savings and low emissions as well as all-round protection of the exhaust aftertreatment system.

Application notes

ALPINE PSA 0W-20 has been specially developed for the most modern engines of the PSA GROUP (Peugeot/Citroën/DS), which require an oil of the PSA B71 2010 standard for Blue HDi, Pure-Tech, hybrid engines or engines with start-stop systems. **ALPINE PSA 0W-20** is also suitable for the car engines of the latest technology that requires an oil according to ACEA C5 SAE 0W-20.

Observe manufacturer's instructions!

Service description

Specifications:

- ACEA C5
- API SP

Recommendations*:

- Fiat 9.55535-DM1
- OPEL OV 040 1547-A20
- PSA B71 2010

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE PSA 0W-20
Density at 15°C	DIN 51 757	kg/m³	845
Viscosity at 40°C	DIN 51 562	mm²/s	43.5
Viscosity at 100°C	DIN 51 562	mm²/s	8.3
Viscosity index (VI)	DIN ISO 2909	-	169
Pour point	DIN ISO 3016	°C	-42
Flash point COC	DIN ISO 2592	°C	232
TBN	DIN ISO 3771	mg KOH/g	10
Sulfated ash	ASTM D874	g/100 g	0.78

^{*} meets the requirements of the OEM manufacturer.

The stated values may vary within the usual commercial range.