

# ALPINE® Special V 0W-30

Synthetic high-performance low viscosity engine oil for Volvo passenger cars

## Properties

**ALPINE Special V 0W-30** is a synthetic high-performance low viscosity engine oil. The lowered HTHS viscosity enables fuel savings in the cold start phase and in short-distance traffic. Guarantees highest engine cleanliness and best wear protection. The product is suitable for use in Volvo passenger cars with the latest efficiency-enhanced Euro 4, 5, 6 engine concepts with or without turbocharger, direct injection, multi-valve or hybrid technology.

**ALPINE Special V 0W-30** guarantees a fuel-saving potential and contributes to the protection of the environment by reducing CO<sub>2</sub> emissions.

## Application notes

**ALPINE Special V 0W-30** is recommended for modern gasoline and diesel engines with the specification VOLVO VCC 95200377.

## Service description

### Specifications:

- ACEA A5/B5
- API SL

### Recommendations\*:

- Volvo VCC 95200377

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Special V 0W-30
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	845
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	52.5
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	9.89
Viscosity Index (VI)	DIN ISO 2909	-	178
Viscosity at -35°C	DIN 51 377	mPa.s	5930
Pour point	DIN ISO 3016	°C	-42
Flash point COC	DIN ISO 2592	°C	224

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.