

# ALPINE® 2-T Special

## Semi-synthetic two-stroke engine oil

### Properties

- Semi-synthetic two-stroke engine oil
- Good protection against rust, corrosion and wear
- Stable lubricating film prevents piston jamming and seizing
- Offers protection against deposits and plug bridging
- Use in systems with separate and mixed lubrication
- Environmentally friendly due to low smoke emission

### Application notes

**ALPINE 2-T Special** is a semi-synthetic two-stroke engine oil for air and water-cooled two-stroke engines in motor vehicles, motorcycles, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.

**Observe manufacturer's instructions.**

### Service description

#### Specifications:

- API TC
- ISO-L-EGD
- JASO FD

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE 2-T Special
Density at 15°C	DIN EN ISO 12185	kg/m <sup>3</sup>	874
Viscosity at 40°C	DIN ISO 51 562	mm <sup>2</sup> /s	62.8
Viscosity at 100°C	DIN ISO 51 562	mm <sup>2</sup> /s	9.1
Viscosity index (VI)	DIN ISO 2909	-	121
Pour point	ASTM D 7346	°C	-39
Flash point COC	DIN ISO 2592	°C	172

\* meets the requirements of the OEM manufacturer.  
The stated values may vary within the usual commercial range.