

ALPINE® ATF MB 15

Low Viscosity HC-Synthetic Automatic Transmission Fluid

Properties

- Reduced viscosity for maximum fuel economy
- High load carrying capacity and extremely wear-reducing
- Superior friction value consistency
- No foam formation
- High thermal stability
- Soft switching operations even at medium temperatures
- Excellent viscosity-temperature behaviour
- Excellent oxidation stability
- Neutral towards common sealing materials

Application notes

- Especially for the latest Mercedes-Benz 7-speed automatic transmission 722.9 with code A89, 7-speed automatic transmission hybrid 724.2, transfer gear box type 205, 213, 217, 218, 222, 238, 253, 257, 290 with transmission 725.0 and transfer gear box type 257 with transmission 725.1
- ATF MB 15 cannot be used in older Mercedes-Benz automatic transmissions and is not backwardly compatible

Observe manufacturer's instructions!

Service description

Recommendation*:

- MB 236.15

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE ATF MB 15
Thickness at 15°C	DIN 51 757	kg/m ³	846
Viscosity 40°C	DIN 51 562	mm ² /s	18.1
Viscosity 100°C	DIN 51 562	mm ² /s	4.4
Viscosity index (VI)	DIN ISO 2909	-	150
Pour point	DIN ISO 3016	°C	-51
Flash point COC	DIN ISO 2592	°C	178
Colour	-	-	blue

August 2020

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.