

ALPINE® Brake Fluid DOT 4 +

High-performance brake fluid

Properties

- Excellent thermal stability
- Synthetic fluid
- Optimum protection of all metal parts of the brake system against corrosion.
- Excellent oxidation stability and reduced hygroscopic properties guarantee a high safety reserve.
- Seal compatible with all seals and hoses used in the brake system.

Application notes

ALPINE Brake Fluid DOT 4 + is for use in very highly stressed brake systems of vehicles for which a synthetic brake fluid according to DOT 4 is prescribed.
Especially recommended for ABS brake systems.
ALPINE Brake Fluid DOT 4 + can be mixed with all synthetic brake fluids of the same quality.

Special notes:

- Store brake fluid only in its original sealed container.
- Brake fluid can cause damage to the vehicle paintwork.

Observe manufacturer's instructions!

Service description

Specifications:

- FMVSS 116 DOT 4
- SAE J 1703 / J 1704
- ISO 4925

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Brake Fluid DOT 4 +
Density at 20°C	DIN 51 757	g/cm ³	1.075
Viscosity -40°C	SAE J1703 / 1704	mm ² /s	Max. 1300
Dry boiling point	SAE J1703 / 1704	°C	265
Wet boiling point	SAE J1703 / 1704	°C	180

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.