

ALPINE® Fliessfett EP 00/000

Multi-purpose EP grease for central lubrication

Properties

- Mixable with most greases based on conventional soaps
- Excellent pumpability even at low temperatures
- Excellent adhesion to metallic surfaces
- Wear-reducing and load-bearing through EP additives
- Water resistant
- Lead, barium and chlorine free
- Oxidation and corrosion resistant

Application notes

ALPINE Fliessfett EP 00/000 is a semi-fluid fluid grease for central lubrication systems of commercial vehicles and stationary machines, as well as in agriculture and forestry or in structural and civil engineering.

When relubricating, care must always be taken to avoid contamination with dust or dirt.

Suitable for Willy Vogel AG central lubrication systems

Observe manufacturer's instructions.

Service description

Specifications:

- DIN 51 826: GP00K-40
- ISO/DIS 6743-9: ISO-L-XDCHB 00

Recommendations:

- MB 264.0
- MAN 283 Li-P 00/000

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Fliessfett EP 00/000
NLGI-Grade	DIN 51 818	-	00
Soap/thickener	-	-	Lithium soap
Colour	visual	-	light green
Texture	visual	-	flat
Use temperature range	-	°C	-40 to +120
Penetration	ISO 2137	0.1 mm	430-440
EMCOR – Test	ISO 51 802	Rating	0-0
Drop point	DIN ISO 2176	°C	>160
Viscosity (base oil) at 40°C	ASTM D 7042	mm ² /s	68
Flow pressure at -35°C	DIN 51 805	hPa	50

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.