

ALPINE® Mehrzweckfett 2

Multipurpose lithium lubricating grease

Properties

- Mixable with most greases based on conventional soaps
- Good adhesion
- Walk- and oxidation-resistant
- Wear-reducing
- Water resistant
- acid-free
- Corrosion prevention

Application notes

ALPINE Multi-Purpose grease 2 is suitable for the lubrication of all types of normally loaded roller and friction bearings as well as joints under normal temperatures and conditions. It is universally applicable in motor vehicles, construction machinery and agricultural equipment.

When relubricating, care must always be taken to avoid contamination with dust or dirt.

Observe manufacturer's instructions.

Service description

Specifications:

- DIN 51 825: K2K-30
- ISO/DIS 6743-9: ISO-L-XCCHA 2

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Mehrzweckfett 2
NLGI-Grade	DIN 51 818	-	2
Soap/thickener	-	-	Lithium soap
Colour	visual	-	natural colour
Texture	visual	-	flat
Use temperature range	-	°C	-30 to +120
Penetration	ISO 2137	0.1 mm	280-300
EMCOR – Test	ISO 51 802	Rating	0-0
Drop point	DIN ISO 2176	°C	190
Viscosity (base oil) at 40°C	ASTM D 7042	mm ² /s	110

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.