

ALPINE® Special F Eco 5W-20

High performance low viscosity engine oil for Ford engines

Properties

ALPINE Special F Eco 5W-20 is a HC-synthetic high-performance, low-viscosity engine oil of latest technology especially for modern Ford EcoBoost engines. Excellent cold-start behaviour ensures optimum lubrication reliability in the cold-running phase. The special additives improve the protection of the catalytic converter. Guarantees highest engine cleanliness and best wear protection. Exceptional product stability enables extended oil change intervals.

ALPINE Special F Eco 5W-20 guarantees a fuel saving potential of up to 3% and contributes to environmental protection by reducing CO₂ emissions.

Application notes

ALPINE Special F Eco 5W-20 was developed especially for the latest Ford EcoBoost engines.

Observe manufacturer's instructions.

Service description

Specifications:

- ACEA C5
- API SN (RC) / CF
- ILSAC GF-5

Recommendations*:

- Chrysler MS-6395
- Fiat 9.55535-CR1
- Ford WSS-M2C948-A/B
- Ford WSS-M2C912-A
- Ford WSS-M2C913-A/B/C
- Ford WSS-M2C925-B
- Jaguar Land Rover STJLR.03.5004

TYPICAL PARAMETERS	METHODS	UNITS	ALPINE Special F Eco 5W-20
Density at 15°C	DIN 51 757	kg/m ³	846
Viscosity at 40°C	DIN 51 562	mm ² /s	44.75
Viscosity at 100°C	DIN 51 562	mm ² /s	8.27
Viscosity index (VI)	DIN ISO 2909	-	162
Pour point	DIN ISO 3016	°C	-42
Flash point COC	DIN ISO 2592	°C	226

* meets the requirements of the OEM manufacturer.
The stated values may vary within the usual commercial range.